

## Schedule 40 Conduit

**UL LISTED**

Conforms to UL 651  
and NEMA TC 2



1. Conduit conforms to UL 651 including 90° C rating and sunlight resistance criteria.
2. All conduit is produced with integral solvent-weld bells. Plain-end conduit may be available.
3. Conduit is produced in 10-foot lengths. 20-foot lengths may be available.
4. Conduit color is gray, except where noted.

Item Number	Trade Size	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
4600500103	1/2	0.840	0.60	0.109	16
4600750103	3/4	1.050	0.80	0.113	22
4601000103	1	1.315	1.03	0.133	32
4601250103	1 1/4	1.660	1.36	0.140	46
4601500103	1 1/2	1.900	1.59	0.145	54
4602000103	2	2.375	2.04	0.154	73
4602500103	2 1/2	2.875	2.44	0.203	120
4603000103	3	3.500	3.03	0.216	170
4603500103	3 1/2	4.000	3.51	0.226	200
4604000103	4	4.500	3.99	0.237	230
4605000103	5	5.563	5.01	0.258	320
4606000103	6	6.625	6.02	0.280	410