

August 2004

### Plain-End Solid-Wall

Nominal Pipe Size (inches)	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')	Length per Crate (feet)	Approximate Crate Weight (lbs)
1½	1.900	1.59	0.145	52	3020	1580
2	2.375	2.04	0.154	70	2100	1480
3	3.500	3.03	0.216	150	1500	2190
4	4.500	3.99	0.237	210	960	2000
6	6.625	6.02	0.280	370	520	1900
8	8.625	7.93	0.322	570	300	1700
10	10.750	9.96	0.365	780	240	1870
12	12.750	11.88	0.406	1030	120	1240

### Belled-End Solid-Wall

Nominal Pipe Size (inches)	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')	Length per Crate (feet)	Approximate Crate Weight (lbs)
4	4.500	3.99	0.237	210	960	2000
6	6.625	6.02	0.280	370	520	1900
8	8.625	7.93	0.322	570	300	1700
10	10.750	9.96	0.365	780	240	1870
12	12.750	11.88	0.406	1030	120	1240

### General Notes:

- Product standard: Solid-wall DWV pipe meets the requirements of ASTM D 2665.
- Material: PVC material meets cell class 12454 per ASTM D 1784.
- Product listing: Solid-wall DWV pipe is listed to the requirements of the Uniform Plumbing Code™.
- Special information:
  - Standard production is in 20-foot lengths; 10-foot lengths may be available.
  - Crate data is for 20-foot lengths.
  - Solid-wall DWV pipe also meets the requirements of ASTM D 1785 for Schedule 40 pressure pipe. The product is listed for potability to ANSI/NSF Standard 61.
- Inside diameters may vary due to allowable manufacturing tolerances.
- Approximate weights are for estimating purposes only.
- Crate weights are for 20-foot lengths.
- All orders are subject to final acceptance by PWEagle sales management.